


ROCKSILK® RS45/RS60/RS80/RS100/RS140

July 2021



APPLICATIONS



DESCRIPTION

Rocksilk® Building Slabs are Rock Mineral Wool slabs in a range of densities, designed for use in multiple thermal and acoustic applications where density is critical. They are non-combustible with the best possible Euroclass A1 reaction to fire classification, and are manufactured using Knauf Insulation's unique bio-based binder, ECOSE® Technology.

PERFORMANCE

Thermal

Thermal conductivity: 0.034 and 0.035 W/mK

Fire

Classification: Euroclass A1 to BS EN 13501-1

Vapour resistivity

Water vapour resistivity: 5.00 MNs/g.m

BENEFITS

- ✓ Single slab can be used for multiple applications.
- ✓ Can be provided with a factory applied foil or tissue facing, offering solutions for a wide variety of applications.

CERTIFICATIONS, CLASSIFICATIONS AND INDUSTRY STANDARDS



ROCKSILK® RS45/RS60/RS80/RS100/RS140

July 2021

SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Length (mm)	Width (mm)	Pieces per pack	Area per pack (m ²)	Packs per pallet	Product code
Rocksilk® RS45							
150	0.035	1200	600	3	2.160	12	531096
100	0.035	1200	600	5	3.600	12	2411339
75	0.035	1200	600	6	4.320	12	2411328
60	0.035	1200	600	8	5.760	12	2411425
50	0.035	1200	600	10	7.200	12	2411327
40	0.035	1200	600	12	8.640	12	2411326
30	0.035	1200	600	16	11.520	12	2411424
25	0.035	1200	600	20	14.400	12	2411325
Rocksilk® RS60							
100	0.034	1200	600	4	2.880	12	2411331
75	0.034	1200	600	6	4.320	12	2411330
60	0.034	1200	600	7	5.040	12	2411433
50	0.034	1200	600	9	6.480	12	2411329
40	0.034	1200	600	12	6.480	12	2411432
25	0.034	1200	600	18	12.960	12	2411430
Rocksilk® RS80							
100	0.034	1200	600	3	2.160	16	2411332
75	0.034	1200	600	4	2.880	16	2411437
50	0.034	1200	600	6	4.320	16	2411435
Rocksilk® RS100							
100	0.034	1200	600	3	2.160	16	2411334
75	0.034	1200	600	4	2.880	16	2411333
50	0.034	1200	600	6	4.320	16	2411441
40	0.034	1200	600	7	5.040	16	2411440
30	0.034	1200	600	10	7.200	16	2411439
25	0.034	1200	600	12	8.640	16	2411438
Rocksilk® RS100 WTF1							
30	0.034	1200	600	10	7.200	16	528143
Rocksilk® RS140							
100	0.034	1200	600	2	1.440	16	2432553
75	0.034	1200	600	3	2.160	10	2411447
50	0.034	1200	600	4	2.880	12	2411446
40	0.034	1200	600	5	3.600	12	2411445
30	0.034	1200	600	7	5.040	10	2411444

ROCKSILK® RS45/RS60/RS80/RS100/RS140

July 2021

ADDITIONAL INFORMATION

Durability

Rocksilk® Building Slabs are odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria. The product will have a life equivalent to that of the wall structure in which it is incorporated.

Application

Rocksilk® Building Slabs are multi-application products for use in built-up metal roofs and walls, pitched roof constructions between rafters, intermediate floors, separating floors, internal stud partitions and light steel frame infill. Rocksilk® Building Slabs are used extensively in OEM applications for fabrication of thermal, acoustic and fire products.

Standards and Certification

Rocksilk® Building Slabs are manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by TÜV Nord.

Real Performance

Glass and Rock Mineral Wool are easier to install correctly than other insulants such as rigid boards because they adapt to any slight imperfections in the substrate and knit together, eliminating any air gaps. Evidence shows the absence of air gaps is crucial to achieving real performance in the relevant application.

Environmental

Rocksilk® Building Slabs contains no ozone-depleting substances or greenhouse gases. For further environmental information consult the relevant Environmental Product Declaration, available on our website.

Handling and storage

Rocksilk® Building Slabs are easy to handle and install, being lightweight and easily cut to size, where necessary. Rocksilk® Building Slabs are supplied in recyclable polythene packs (4-LDPE) which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Rocksilk® Building Slabs should not be left permanently exposed to the elements.



ECOSE Technology is our unique bio-based binder, that is used in the manufacture of all of our Glass Mineral Wool products and the majority of our Rock Mineral Wool products, to bind insulation strands together. ECOSE Technology contains no added formaldehyde or phenol. It is made from natural raw materials that are rapidly renewable and is 70% less energy-intensive to manufacture than traditional binders, so it is more environmentally-friendly. Products made with ECOSE Technology are soft to touch and easy to handle. They generate low levels of dust and VOCs and have been awarded the Eurofins Gold Certificate for Indoor Air Comfort..

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,
Merseyside, WA10 3NS. UK

Customer Service: 01744 766 766 Technical Support Team: 01744 766 666

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatsoever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE2980DAT-V0721

challenge.
create.
care.