



## **Declaration of Performance**

Kingspan GreenGuard® GG700 1001.CPR.2013.GG700.004

Unique identification code of the product-type:

Intended use/es:

Manufacturer: System/s of AVCP:

Harmonised technical specification:

Notified body/ies:

Kingspan GreenGuard® GG700 Thermal Insulation for buildings

Kingspan Insulation Ltd, Herefordshire HR6 9LA,UK System 4 (Reaction to fire), System 3 (Other Properties)

EN 13164:2012+A1:2015

LNEC: 0856

Essential charac	teristics	Performance
Thermal resistance	Thermal resistance R <sub>D</sub> ((m².K)/W)	d <sub>N</sub> 40mm 1.20   d <sub>N</sub> 50mm 1.40   d <sub>N</sub> 60mm 1.70   d <sub>N</sub> 70mm 2.00   d <sub>N</sub> 80mm 2.25   d <sub>N</sub> 100mm 2.70   d <sub>N</sub> 110mm 2.95   d <sub>N</sub> 120mm 3.20
	Thermal conductivity λ <sub>D</sub> (W/(m².K))	$\begin{array}{ccc} d_N40mm & 0.033 \\ d_N50mm - 80mm & 0.035 \\ d_N{\geq}100mm & 0.037 \end{array}$
	Dimensional tolerances	Т1
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability characteristics	NPD
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensional stability under specified temperature and humidity conditions	DS(70,90)
	Deformation under specified compressive load and temperature conditions	NPD
Compressive strength	Compressive stress or compressive strength	CS(10/Y)700
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Waterpermeability	Long term water absorption by total immersion	NPD
	Long term water absorption by diffusion	NPD
	Freeze-thaw resistance after long term water absorption by diffusion	NPD
Water vapour permeability	Watervapourtransmission	NPD
Closed cell content	Closed cell content	NPD
Continuous Glowing combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD





## **Declaration of Performance**

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

iven der

Aiveen Kearney Managing Director Pembridge, England, UK

Date signed: 17/08/2022 Issue Number: 004



For the most up-to-date version of the Declaration of Performance please scan or click here.

To access pre-existing product information or information relating to previously sold/discontinued products please email literature@kingspaninsulation.co.uk