



Declaration of Performance

Kingspan Kooltherm® K110 Soffit Board

1000.CPR.2013.K110.006

Unique identification code of the product-type:
Intended use/es:
Manufacturer:
System/s of AVCP:
Harmonised technical specification
Notified body/ies:

Kingspan Kooltherm® K110 Soffit Board
Thermal insulation for buildings
Kingspan Insulation Ltd, Herefordshire HR6 9LA, UK
System 1 (Reaction to Fire), System 3 (Other Properties)
BS-EN 13166:2012+A2:2016
Efectis NB :1812, KIWA NB:0063. FIW München NB: 0751

Essential characteristics		Performance																		
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	<table> <tr><td>d_N 65mm</td><td>3.40</td></tr> <tr><td>d_N 70mm</td><td>3.65</td></tr> <tr><td>d_N 75mm</td><td>3.90</td></tr> <tr><td>d_N 80mm</td><td>4.20</td></tr> <tr><td>d_N 85mm</td><td>4.45</td></tr> <tr><td>d_N 90mm</td><td>4.70</td></tr> <tr><td>d_N 100mm</td><td>5.25</td></tr> <tr><td>d_N 110mm</td><td>5.75</td></tr> <tr><td>d_N 120mm</td><td>6.30</td></tr> </table>	d_N 65mm	3.40	d_N 70mm	3.65	d_N 75mm	3.90	d_N 80mm	4.20	d_N 85mm	4.45	d_N 90mm	4.70	d_N 100mm	5.25	d_N 110mm	5.75	d_N 120mm	6.30
	d_N 65mm	3.40																		
	d_N 70mm	3.65																		
d_N 75mm	3.90																			
d_N 80mm	4.20																			
d_N 85mm	4.45																			
d_N 90mm	4.70																			
d_N 100mm	5.25																			
d_N 110mm	5.75																			
d_N 120mm	6.30																			
Thermal conductivity λ_D (W/(m.K))	λ_D 0.019																			
Thickness tolerance	T1																			
Reaction to fire	Reaction to fire	C-s2,d0																		
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability Characteristics	NPD																		
Durability of thermal resistance against heat, weathering, ageing/ degradation	Durability Characteristics	NPD																		
	Dimensional stability under specified temperature and humidity condition	DS(70,90)																		
		DS(-20,-)																		
Determination of the aged values of thermal resistance and thermal conductivity	R_D and λ_D																			
Compressive strength	Compressive stress or compressive strength	CS(Y)100																		
Tensile / Flexural strength	Tensile strength perpendicular to faces	NPD																		
Durability of compressive strength against ageing / degradation	Compressive creep	NPD																		



Declaration of Performance

Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Closed cell content	CV
Water vapour permeability	Water vapour transmission	NPD
	Closed cell content	CV
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

For System 1 AVCP Notified certification body No 1812 Performed, carried out the determination of the product type, the inspection of the manufacturing plant and factory production control and continuous surveillance, assessment and evaluation of the factory production control, and issued the certificate of constancy of performance for reaction to fire, cert No 1812 – CPR - 1992

Notified testing lab 0063 and 0751 Performed the test reports for the other relevant declared characteristics (AVCP 3 properties).

Signed for and on behalf of the manufacturer by:

.....
Aiveen Kearney
Managing Director UK and Ireland
Pembridge, England, UK
Date Signed: 08/08/2022
Version Number: 006

K\IGB\CPRDoP\K110\006\Aug22a