

## LOFT ROLL 40 AND 44

March 2022

### APPLICATIONS



### DESCRIPTION

Knauf Insulation Loft Rolls are Glass Mineral Wool rolls, designed for use in cold lofts where pitched roofs are insulated at ceiling level.

They are non-combustible with the best possible Euroclass A1 reaction to fire classification, and are manufactured using Knauf Insulation's unique bio-based binder, ECOSE® Technology.

### BENEFITS

- ✓ Available Combi-cut, Ready-cut and uncut formats giving a wide range of choice to suit specific install requirements.
- ✓ Combi-cut products are supplied partially perforated, providing the flexibility to be used between joists or used uncut as a full-width roll as a top-up layer, maximising on-site efficiency.
- ✓ Manufactured in two different options; long lengths to allow quick and simple installation maximising efficiency, and shorter lengths for ease of handling on-site.
- ✓ Compression packed and lightweight for easy handling and moving around a site.

### PERFORMANCE

#### Thermal

Thermal conductivity: 0.040 and 0.044 W/mK

#### Fire

Classification: Euroclass A1 to BS EN 13501-1

#### Vapour resistivity

Water vapour resistivity: 5.00MNs/g.m.

### SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m <sup>2</sup> K/W)	Length (mm)	Width (mm)	Area per pack (m <sup>2</sup> )	Packs per pallet	Product code
<b>Loft Roll 44 (Combi-cut)</b>							
200	0.044	4.50	6000	1140 (2x570/3x380)	6.840	24	715820
170	0.044	3.85	7030	1140 (2x570/3x380)	8.014	24	2404156
150	0.044	3.40	8050	1140 (2x570/3x380)	9.177	24	2404155
100	0.044	2.25	12180	1140 (2x570/3x380)	13.885	24	2404154
<b>Loft Roll 44 Short Length (Combi-cut)</b>							
200	0.044	4.50	4825	1140 (2x570/3x380)	5.529	30	244329
170	0.044	3.85	5700	1140 (2x570/3x380)	6.498	30	244328
150	0.044	3.40	6450	1140 (2x570/3x380)	7.353	30	244327
100	0.044	2.25	9725	1140 (2x570/3x380)	11.087	30	244326

All dimensions are nominal

### CERTIFICATIONS, CLASSIFICATIONS AND INDUSTRY STANDARDS



## LOFT ROLL 40 AND 44

March 2022

### SPECIFICATIONS

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m <sup>2</sup> K/W)	Length (mm)	Width (mm)	Area per pack (m <sup>2</sup> )	Packs per pallet	Product code
<b>Loft Roll 44 (Ready-cut)</b>							
150	0.044	3.40	8050	2x570	9.177	24	2404163
100	0.044	2.25	12180	2x570	13.885	24	2404161
<b>Loft Roll 44 (Uncut)*</b>							
200	0.044	4.55	6000	1140	6.840	24	TBC
150	0.044	3.41	8050	1140	9.177	24	2438878
100	0.044	2.27	12800	1140	14.592	24	2438877

All dimensions are nominal  
\*Uncut rolls only available in Ireland

Thickness (mm)	Thermal conductivity (W/mK)	Thermal resistance (m <sup>2</sup> K/W)	Length (mm)	Width (mm)	Area per pack (m <sup>2</sup> )	Packs per pallet	Product code
<b>Loft Roll 40 (Combi-cut)</b>							
200	0.040	5.00	4850	2x570/3x380	5.529	24	2404169
150	0.040	3.75	7530	2x570/3x380	8.584	24	2404166
100	0.040	2.50	11250	2x570/3x380	12.825	24	2404167

All dimensions are nominal

## LOFT ROLL 40 AND 44

March 2022

### ADDITIONAL INFORMATION

#### Durability

Loft Rolls are odourless, rot proof, non-hygroscopic, do not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

#### Application

Loft Rolls are used for the thermal insulation of cold pitched roofs at ceiling level. They are usually laid in two layers, with the first layer between the joists and the second layer over, and at right angles to the joists.

#### Standards and certification

Loft Rolls are manufactured in accordance with BS EN 13162, ISO 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management systems, as certified by TÜV Nord. All our Glass Mineral Wool products have been awarded the DECLARE 'Red List Free' label. Having the 'Red List Free' label means that there are no ingredients in the product that are on the red list - including formaldehyde or phenol

#### Real performance

Glass and Rock Mineral Wool are easier to install correctly than other insulants such as rigid boards because they adapt to any slight imperfections in the substrate and knit together, eliminating any air gaps. Evidence shows the absence of air gaps is crucial to achieving real performance in the relevant application.

#### Environmental

Loft Rolls contain no ozone-depleting substances or greenhouse gases. For further environmental information consult the relevant Environmental Product Declaration, available on our website.

#### Handling and storage

Loft Rolls are easy to handle and install, being lightweight and easily cut to size, where necessary. Loft Rolls are supplied in recyclable polythene packs (4-LDPE) which are designed for short term protection only. For longer term protection on site, the product should either be stored indoors, or under cover and off the ground. Loft Rolls should not be left permanently exposed to the elements.



ECOSE® Technology is our unique bio-based binder, that is used in the manufacture of all of our Glass Mineral Wool products and the majority of our Rock Mineral Wool products, to bind insulation strands together. ECOSE® Technology contains no added formaldehyde or phenol. It is made from natural raw materials that are rapidly renewable and is 70% less energy-intensive to manufacture than traditional binders, so it is more environmentally-friendly. Products made with ECOSE® Technology are soft to touch and easy to handle. They generate low levels of dust and VOCs and have been awarded the Eurofins Gold Certificate for Indoor Air Comfort.

#### Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,  
Merseyside, WA10 3NS. UK

Customer Service: 01744 766 766      Technical Support Team: 01744 766 666

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatsoever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE1508DAT-V0322

challenge.  
create.  
care.